

**IN THE CLAIMS:**

Please examine claims 1-30 found in the translation of the Amended Sheets attached to the International Preliminary Report on Patentability.

The following is a complete listing of claims in this application.

1. (currently amended) A carrier (10, 38, 100) for structural parts to be subjected to a heat-treatment process, comprising at least one frame (11, 40, 102, 104, 106, 108, 110) and a lattice (20, 50, 112, 114, 116, 118, 120) ~~consisting of~~ comprising intersecting strands proceeding therefrom, wherein the frame comprises one or more limbs (12, 14, 16, 18, 42, 44, 46, 48, 121, 122, 124, 125, 126, 128, 130, 132, 134, 136, 138, 140) preferably forming a polygon, and wherein the frame (11, 40, 102, 104, 106, 108, 100) comprises temperature-resistant material and the strands of carbon fibers or ceramic fibers which form the lattice (20, 50, 112, 1414, 116, 118, 120) extending from the limb or pieces (12, 14, 18, 42, 44, 46, 48, 121, 122, 124, 125, 126, 128, 130, 132, 134, 136, 138, 140) of the frame,

characterized in that the lattice (20, 50) is formed by a section of an endless fiber bundle extending between limbs (12, 14, 16, 18, 42, 44, 46, 48) of the frame in the form of single-layer or multilayer fiber strands or intertwined yarns of a carbon-reinforced carbon material and/or ceramic material, the fiber bundle extending in a warp and woof-like woven structure between the limbs of the frame.

2. (original) The carrier according to claim 1, characterized in that the limbs (12, 14, 16, 18, 42 44, 46, 48) of the frame extend at a right angle to the plane formed by the lattice (20, 50).

3. (original) The carrier according to claim 2,

characterized in that the carrier (100) comprises several frames (102, 104, 106, 108, 100) forming a three-dimensional body and, in particular, has a basket geometry.

4. (currently amended) The carrier according to ~~at least~~ claim 1, characterized in that the limbs (12, 14, 16, 18) have recesses in their respective longitudinal edges, sections of the fiber bundle passing through said recesses to mount the lattice (20, 50).

5. (original) The carrier according to claim 4, characterized in that the recesses form a ridge-like geometry in the respective longitudinal edge (24, 26, 28, 30) of the limb (12, 14, 16, 18) of the frame.

6. (currently amended) The carrier according to ~~at least~~ claim 1, characterized in that the limbs (42, 44, 46, 48) of the frame (40) have openings such as bores (52, 54) through which the fiber bundle passes.

7. (currently amended) The carrier according to ~~at least~~ claim 1, characterized in that the fiber bundle laid in the woven structure extends under prestress between the limbs (12, 14, 16, 18, 42, 44, 46, 48).

8. (currently amended) The carrier according to ~~at least~~ claim 1, characterized in that the frame (11, 52) is integrally cut out of a carbon fiber-reinforced carbon plate.

9. (currently amended) The carrier according to ~~at least~~ claim 1, characterized in that the limbs (42, 44, 46, 48) forming the frame (40) are joined together by means of plug connections.

10. (currently amended) The carrier according to ~~at least~~ claim 1, characterized in that the base of the frame (11, 38) or its limbs (12, 14, 16, 18, 42, 44, 46, 48) is a pyrolyzed fiber preform produced by means of TFP technology.

11. (currently amended) The carrier according to ~~at least~~

claim 1, characterized in that the frame (11, 40) comprises a section or sections separated, in particular, by means of water jet cutting from a carbon fiber-reinforced carbon plate, such as a CFC plate.

12. (currently amended) The carrier according to ~~at least~~ claim 1, characterized in that the fiber material comprises or contains  $\text{Al}_2\text{O}_3$  and/or SiC and/or BN and/or C.

13. (currently amended) The carrier according to ~~at least~~ claim 1, characterized in that the lattice (20, 50) has a matrix which comprises or contains carbon,  $\text{B}_4\text{C}$ ,  $\text{Al}_2\text{O}_3$ , SiC,  $\text{Si}_3\text{N}_4$  and/or mullite.

14. (original) The carrier according to claim 13, characterized in that the matrix is separated from the gas phase and/or formed by pyrolysis of a precursor material.

15. (original) The carrier according to claim 14, characterized in that the precursor material is phenolic resin and/or furan resin and/or a Si precursor.

16. (currently amended) The carrier according to ~~at least~~ claim 1, characterized in that at least the lattice has or contains a coating of oxides, nitrides and/or carbides of the third and fourth main group and/or third to sixth subgroup of the periodic system and/or carbon.

17. (currently amended) The carrier according to ~~at least~~ claim 1, characterized in that the frame (11, 40) comprises carbon fiber-reinforced carbon, fiber ceramic or graphite.

18. (currently amended) The carrier according to ~~at least~~ claim 1, characterized in that the carrier (100) has a parallelepiped geometry open on one side with bottom and side frames (102, 104, 106, 108, 110) which are each holders for a lattice (112, 114, 116, 118, 120).

19. (currently amended) The carrier according to ~~at least~~ claim 18, characterized in that the upper limb (121, 122, 124,

125) of each side frame (112, 114, 116, 118) is a flat element and/or the lower limb (126, 128, 130, 132) of each side frame is an angular element and/or limbs (134, 136, 138, 140) at a right angle thereto are each a round element.

20. (currently amended) The carrier according to ~~at least~~ claim 19, characterized in that the flat element forms, with its flat side, a plane in which or in approximately which the lattice (112, 114, 116, 118) fixed by the frame (102, 104, 106, 108) extends.

21. (currently amended) The carrier according to ~~at least~~ claim 19, characterized in that the respective flat element (121, 122, 124, 125) of the side frame (112, 114, 116, 118) passes over in a flush manner into the respective front end of a round element (134, 136, 138, 140) on the outer longitudinal peripheral side.

22. (currently amended) The carrier according to ~~at least~~ claim 19, characterized in that adjoining flat elements of rectangular or approximately rectangular abutting frames (102, 104, 106, 108) are connected via a plug connection which, in turn, extends within one of the round elements (134, 136, 138, 140).

23. (currently amended) A method for producing a structural part ~~consisting of~~ comprising intersecting strands of carbon fibers or ceramic fibers using a frame composed of one or more limbs, from which an endless fiber bundle in the form of single-layer or multilayer fiber strands or intertwined yarns are mounted accordingly as the strands to form a desired lattice structure, that a matrix is then inserted into the fibers and the lattice subsequently removed from the frame.

24. (original) The method according to claim 23, characterized in that the lattice is separated, e.g. cut off,

from its sections extending from the frame.

25. (original) The method according to claim 23, characterized in that the matrix is separated from the gas phase and/or formed by pyrolysis of one or more precursor materials.

26. (original) The method according to claim 23, characterized in that the lattice is coated on the surface prior to and/or after removal of the lattice from the frame.

27. (currently amended) The method according to ~~at least~~ claim 23, characterized in that  $\text{Al}_2\text{O}_3$  and/or SiC and/or BN and/or C is used as fibers or fiber material.

28. (currently amended) The method according to ~~at least~~ claim 23, characterized in that carbon and/or  $\text{B}_4\text{C}$  and/or  $\text{Al}_2\text{O}_3$  and/or SiC and/or  $\text{Si}_3\text{N}_4$  and/or mullite is used as matrix material.

29. (currently amended) The method according to ~~at least~~ claim 26, characterized in that the lattice is surface-coated with oxides, nitrides and/or carbides of the third and fourth main group and/or third to sixth subgroup of the periodic system and/or carbon.

Claim 30 (canceled).